

**skai®**

IC 2  
N 0  
A 1  
RDS 7  
INTERIOR  
INNOVATION  
winner

**if**  
DESIGN  
AWARD  
2017



Textile Design

skai® Paratexa NF

***FR-B1 Textile Design***




Interior




# FR-B1 Textile Design

skai® Paratexa NF




skai® Paratexa NF




## skai® Paratexa NF

skai® Paratexa NF ist ein hochwertiger Polsterbezugsstoff mit einer sehr authentischen Textiloptik. Das Material überzeugt durch die Erfüllung der anspruchsvollen B1-Flammschutznorm und ist ideal für den Einsatz im Objektbereich geeignet. Die trendige Farbauswahl, eine angenehme Haptik und eine extrem detaillierte Textilprägung machen skai® Paratexa NF zum echten Premiumprodukt.

skai® Paratexa NF is a high-quality upholstery material with a very realistic textile look. The material is notable due to its compliance with the rigorous B1-flame resistance standard and is therefore ideal for use in the contract area. The trendy colours, pleasant feel, and extremely detailed embossing make skai® Paratexa NF a genuine premium product.




skai® Paratexa NF silvergrey F6411209




honeydew melon F6411200



pearl F6411201



birch F6411202




silvergrey F6411209




arctic blue F6411210




sapphire F6411211




powder rose F6411203




coral F6411204




choco F6411205




pewter F6411212




anthracite F6411213




black F6411214



seafoam green F6411206



tourmaline F6411207



fango F6411208



# FR-B1 Textile Design



contract



hospitality



residential



healthcare

## Technische Eigenschaften

### Materialzusammensetzung:

ca. 85% PVC-Compound, ca. 15% BW-Gestrick

**Gewicht:** 780 +/- 50 g/m<sup>2</sup>, **Dicke:** 1,3 +/- 0,2 mm

**Rollenbreite:** 137 cm, **Rollenlänge:** 30 m



langlebig



lichtecht

DIN EN ISO 105-B02, Stufe 6



reißfest



pflegeleicht



blut- und urinbeständig



desinfektionsmittelbeständig



abriebfest

DIN EN ISO 5470-2: > 30.000 Martindale



**DIN 4102-1 (Part 1, B1)**, NF M1, AM 18,  
BS5852 IS-0+1+5, EN1021-1+2, DIN53438 (Part 2)  
MVSS302, UNI 9175/87 (1.IM)



IMO FTPC P8

## Anwendung / Verarbeitung

Geeignet für viele Arten von Bepolsterungen und Bespannungen in der Polsterindustrie. Besonders geeignet für den Einsatz im trendorientierten Wohn- und Objektbereich, in öffentlichen Gebäuden und Einrichtungen. Problemlose Verarbeitung nach den üblichen Verfahren (Nähen, Heften, Kleben, Nageln). Keine Lösemittelkleber verwenden!

## Sonstige Hinweise

Für dauerhafte Freude an ihrem **skai**<sup>®</sup> Material bitte regelmäßig reinigen. Verschmutzungen durch Öle, Fette und Tinte müssen umgehend entfernt werden. Benutzen Sie hierzu eine warme, milde Seifenlauge und ein Mikrofasertuch oder eine weiche Handbürste. Bitte keine Lösemittel, Chloride, Poliermittel, chemische Reinigungsmittel oder Wachspoliermittel einsetzen. Bitte beachten sie, dass Abfärbungen durch Jeans oder andere Textilien von jeglicher Herstellergarantie ausgenommen sind.

## Besondere Hinweise

Unsere anwendungstechnischen Empfehlungen in Wort und Schrift, die wir aufgrund unserer Erfahrung entsprechend dem aktuellen Kenntnisstand weitergeben, sind unverbindlich und begründen kein Rechtsverhältnis und keine Nebenverpflichtungen aus dem Kaufvertrag. Sie entbinden den Käufer nicht davon, unsere Produkte für den vorgesehenen Verwendungszweck in eigener Verantwortung selbst zu prüfen. Im Übrigen gelten unsere allgemeinen Geschäftsbedingungen. Hiermit verlieren alle früheren, anderslautenden Regelungen ihre Gültigkeit.

## Technical properties

### Material composition:

approx. 85% PVC-compound, approx. 15% CO-knitted fabric

**weight:** 780 +/- 50 g/m<sup>2</sup>, **thickness:** 1.3 +/- 0.2 mm

**roll width:** 137 cm, **roll length:** 30 m



long-lasting



lightfast

DIN EN ISO 105-B02, level 6



tear-resistant



easy to clean



blood- and urine resistant



resistant to disinfectants



abrasion resistant

DIN EN ISO 5470-2: > 30.000 Martindale



**DIN 4102-1 (Part 1, B1)**, NF M1, AM 18,  
BS5852 IS-0+1+5, EN1021-1+2, DIN53438 (Part 2)  
MVSS302, UNI 9175/87 (1.IM)



IMO FTPC P8

## Application / Processing

Suitable for many kinds of upholsteries and coverings in the upholstery industry. Especially suitable for the use in the modern residential and contract area, in public buildings and institutions. Problem-free processing in the usual procedures (sewing, tacking, sticking, nailing). Do not use solvent-based adhesives!

## Other instructions

For durable joy with your **skai**<sup>®</sup> material, please clean regularly. Pollution by oil, fat and ink must be removed immediately. Clean with warm, mild soap lye and a micro-fibre cloth or a soft hand brush. Please, do not use solvents, chloride, abrasives, chemical cleaning agents or wax polishes. Please note that colorings by jeans or other textiles are excluded from any manufacturer's guarantee.

## Special notes

Our written and spoken technical recommendations, which we provide based on our experience in accordance with the current state of knowledge, are nonbinding and do not constitute a legal relationship and are not additional obligations from the purchase agreement. They do not release the purchaser from checking our products for the intended use under his own responsibility. Otherwise, our general terms and conditions are in effect. All earlier provisions to the contrary hereby become invalid.



ISO 9001  
ISO 14001  
ISO 50001



\* nach den gesetzlichen Bestimmungen  
prescribed by law